

BOBKOV, A.S.

Technical standardisation in Russian building in the prerevolutionary period. Trudy Inst. ist.est. i tekhn. 7:255-262 '56. (MLRA 9:9)
(Building--Production standards)

BOBKOV, A. S. kandidat tekhnicheskikh nauk.

Masonry work. Streitel' 2 no.8:29 Ag '56.
(Masonry)

(MLRA 9:12)

BOBKOV, A.^{S.}, kandidat tekhnicheskikh nauk.

Fedor Kon', the master city builder. Strpitel' 2 no. 10:30 0 '56.
(MIRA 10:1)
(Kon', Fedor Savel'evich)

BOBKOV, A.S.

Brief survey of British and American literature of the history of
construction engineering. Vop. 1st. est. 1 tekhn. no.3:251-255 '57.
(England--Engineering--History) (MIRA 11:1)
(United States--Engineering--History)

BAKAYEV, V.A.; BOBKOV, A.S.

First Congress of the International Council on Construction.
Prom.stroi. 38 no.1:63-64 '60. (MIRA 13:5)
(Rotterdam--Building--Congresses)

BOBKOV, A.S., Inzh.

Safety measures in the explosive forming of parts. Khim. i
neft. mashinost. no. 5:36-38 N 164 (MIRA 1882)

BOBKOV, Anatoliy Sergeevich, kand. tekhn. nauk, dots.; TRUBIN,
V.A., prof. [deceased , retsenezent; MARTYNOV, A.P.; red.

[Principles of the construction of industrial buildings
and structures for the chemical industry] Osnovy stroitel'-
stva promyshlennykh zdaniy i sooruzheniy khimicheskoi pro-
myshlennosti. Moskva, Vysshaya shkola, 1965. 263 p.
(MIRA 18:7)

BOBKOV, A.S.

Safety measures in explosive forming. Mashinostroitel' no.10:
40-41 0 '63. (MIRA 16:12)

L 16329-65 EWT(m)/EWA(d)/EWP(k)/EWP(t)/EWP(b) Pf-4 JD/HW

ACCESSION NR: AP4049182

S/0314/64/000/005/0036/0038

AUTHOR: Bobkov, A.S. (Engineer)

TITLE: Precautions during the stamping of parts by blasting 4

SOURCE: Khimicheskoye i neftyanoye mashinostroyeniye, no. 5, 1964, 36-38

TOPIC TAGS: stamping, blasting stamping, blasting safety

ABSTRACT: Publications have recently been appearing describing the underwater blasting of parts in order to stamp them using comparatively small explosive charges instead of large presses. The explosive is detonated in a well lined with steel plates. The billet to be stamped is placed on a steel die, ensuring uniform tension of the flange by a V-1 colloidal-graphite compound. The explosive together with the cap is placed above the billet and the well is filled with water. When the required vacuum of 5-10 mm Hg is reached, the detonator is wired. Certain precautions have been found necessary, however, and are satisfied by the following measures. A reliable blocking circuit must be made for safety of the personnel. Optimal water filtration should be assured after blasting. The seismic action on the building should be investigated, and the damping of the water above the well should be calculated. Ventilation of harmful gases should be

Card 1/2

L 16329-65

ACCESSION NR: AT4049182

guaranteed and ground currents should be eliminated. Safety should also be assured during the storage and handling of explosives. A charge of TNT weighing not over one kg may be used for blasting parts in water poured into a 3.6 m diameter steel cylinder 3.6 m in height with a wall thickness of 16 mm. The paper includes diagrams of two types of circuits for ensuring the required precautions. If no explosion follows after the blasting circuit has been closed, it is prohibited to approach the explosive for 5-10 minutes. A table is included showing the allowable distances that radio transmitters should be located from the blasting circuit. For example, a distance of 2100 m is required for a 50,000-100,000 watt radio transmitter. Orig. art. has: 3 figures and 1 table.

ASSOCIATION: none

SUBMITTED: 00

ENCL: 00

SUB CODE: MM, WA

NO REF SOV: 000

OTHER: 000

Card 2/2

S/190/62/004/011/007/014
B106/B101

AUTHORS: Shilov, A. Ye., Shilova, A. K., Bobkov, B. N.

TITLE: Reaction of α -olefins with soluble complex Ziegler catalysts and the mechanism of polymerization initiation


PERIODICAL: Vysokomolekulyarnyye soyedineniya, v. 4, no. 11, 1962, 1688 - 1695

TEXT: In a previous paper (Ref. 3: A. K. Zefirova, A. Ye. Shilov, Dokl. AN SSSR, 136, 599, 1961) the hypothesis was put forward that the polymerization of ethylene is initiated by an ionic mechanism in the presence of a Ziegler catalyst obtained by bringing dicyclopentadienyl titanium into reaction with aluminum alkyls. This hypothesis was studied experimentally on the basis of the catalytic system $(C_5H_5)_2TiCl_2-Al(CH_3)_2Cl$. Since the polymerization of ethylene coincides with the reduction of Ti^{4+} to Ti^{3+} , which is accompanied by a change in color, the process was studied by spectrophotometry. Titanium is reduced by reaction of $(C_5H_5)_2TiCl_2$ with $Al(CH_3)_2Cl$ only in the presence of α -olefins (studied in

Card 1/3

Reaction of α -olefins...S/190/62/004/011/007/014
B106/B101

n-heptene-1 as an example). The following course of reaction resulted from kinetic investigations:



conversions of complex A take place; the resulting compounds do not react with α -olefins. The polymerization rate of ethylene in the $(\text{C}_5\text{H}_5)_2\text{TiCl}_2\text{-Al}(\text{CH}_3)_2\text{Cl}$ system as well as the rate of titanium reduction in this system in the presence of an α -olefin are directly proportional to the increase in electrical conductivity due to the formation of the complex A. These results confirm that the Ti reduction in the presence of an α -olefin, as well as the initiation of polymerizations in the system studied, have an ionic mechanism. This does not agree with the results obtained by J. C. W. Chien (J. Amer. Chem. Soc., 81, 86, 1959). The mechanism of Ti reduction is analogous to that indicated in Ref. 3 for the reduction of $(\text{C}_5\text{H}_5)_2\text{TiCl}_2$ by $\text{Al}(\text{C}_2\text{H}_5)_2\text{Cl}$. The sole difference is that in the case of $\text{Al}(\text{C}_2\text{H}_5)_2\text{Cl}$ the intramolecular disproportioning of the two

Card 2/3

Reaction of α -olefins...

S/190/62/004/011/007/014
B106/B101

ethyl groups can start without preliminary incorporation of the olefin. A rough estimate of the ion concentration in the reaction studied (using benzene as a solvent) with the aid of the Walden equation yielded

$\sim 5 \cdot 10^{-9}$ mole/l for medium concentrations of complex A of $\sim 5 \cdot 10^{-3}$ mole/l. Hence, the concentration of ions is very low and their reactivity very high. There are 5 figures. The most important English-language references are: W. P. Long, D. S. Breslow, J. Amer. Chem. Soc., 82, 1953, 1960; A. N. Maki, E. W. Randall, J. Amer. Chem. Soc., 82, 4109, 1960; G. Wilkinson, J. M. Birmingham, J. Amer. Chem. Soc., 76, 4281, 1954. ✓

ASSOCIATION: Institut khimicheskoy fiziki AN SSSR (Institute of Chemical Physics AS USSR)

SUBMITTED: June 30, 1961

Card 3/3

BOBKOV, I.

For 3700 kilograms of milk! Nauka i pered. op. v sel'khoz. 8
no.4:15-17 Ap '58. (MIRA 11:5)

1. Predsedatel' Ryazanskogo oblispelkoma.
(Dairying)

BOBKOV, I.G.

Diagnosis of defects of the interauricular septum. *Pediatria*
38 no.9:15-20 S '60. (MIRA 13:12)

1. Iz kafedry gosptal'noy khirurgii (sav. - deystvitel'nyy
chlen AMN SSSR prof. B.V. Petrovskiy) I Moskovskogo meditsin-
skogo instituta imeni I.M. Sechenova.
(HEART--ABNORMITIES AND DEFORMITIES)

BOBKOV, I.G.

Experimental defects of the interauricular septum. Eksp.khir.1
anest. 6 no.1:37-43 '61. (MIRA 14:10)
(HEART--ABNORMITIES AND DEFORMITIES)

1. BOEKOV, I. N.
2. USSR (600)
4. Lithuania - Agriculture
7. Introducing the achievements of science and progressive practice on collective farms of Lithuania, Dost. sel'khoz, no. 4, 1953.

9. Monthly List of Russian Accessions, Library of Congress, April 1953, Uncl.

BOBKOV, I.N., inzh.

Production of dehydrated phosphorobacterin. izbor. 1 rats. 3
no. 4:6-7 Ap '58. (MIRA 11:7)

(Fertilizers and manures)

BOBKOV, I.N., inzh.

Unit for ripping brushwood. Trakt. i sel'khoz mash. no.2:33-34
F '59. (MIRA 12:1)

(Plows)

BOBKOV, I.N., inzh.

Silicate plowshare. Trakt.1 sel'khozmasb. 30 no.2:27-28
F '60. (MIRA 13:5)

(Flows)

BOBKOV, I.P.

Convulsive hysterical attacks. Trudy Inst.klin. i eksp.khir.
AN Kazakh.SSR no.7:55-62 '61. (MIRA 15:3)

(HYSTERIA)

(CONVULSIONS)

BOBKOV, I. V.
BOBKOV, I. V.

From the Ryazan of the landlords to a socialist province. Zhivotno-
vodstvo 19 no.11:12-18 N '57. (MIRA 10:12)

1. Predsedatel' Ryazanskogo oblispolkoma.
(Ryazan Province--Stock and stockbreeding)

22(1)

SOV/3-59-4-16/42

AUTHORS: Bobkov, K.I., and Nazarov, V.V., Candidates of Economic Sciences

TITLE: To Develop Research in the Field of Political Economy

PERIODICAL: Vestnik vysshey shkoly, 1959, Nr 4, pp 41-46 (USSR)

ABSTRACT: Economic sciences as one of the factors of fast development of Socialist economy will assume increased importance within the 7-Year Plan. Workers of the Chairs of Political Economy will have to take an active part in composing fundamental works generalizing the regularities of economic development processes and of the practice of building of Socialism. The author quotes a number of examples confirming the successful scientific activity of the Chairs and individual instructors of political economy. However, the author considers that in a great number of vuzes the scientific work does not as yet conform to the increased demands of both the present and the future. In this connection he deals with the problem of increasing the scientific qualification of instructors, pointing out that only very few instructors are preparing theses

Card 1/4

SOV/3-59-4-16/42

99 Develop Research in the Field of Political Economy

for a Doctor's degree. In Kazan', e.g., where there are 10 higher educational institutions, including such big ones as the University and the Finansovo-ekonomicheskii institut (Finance-Economic Institute), not a single instructor of political economy is working on a thesis for a Doctor's degree. In Kuybyshev, having 7 vuzes including the Planovyy institut (Planning institute), which turns out economists for various branches of national economy, only one thesis is being prepared. Moreover, the themes of the dissertations sometimes bear a much ~~too~~ general character. The author cites ~~this~~ themes originating ~~from~~ students of the Kiyevskiy meditsinskii institut (Kiev Medical Institute), Leningradskiy pedagogicheskii institut (Leningrad Pedagogical Institute) and the Saratovskiy sel'skokhozyaystvennyy institut (Saratov Agricultural Institute). Speaking of the dissertation of thesis themes, the author mentions Docent V.M. Raud of the Leningrad University and Instructor I.K. Aleksandrov of the Partiynaya shkola (Party School), who worked on the same theme. In this connection the author states a number of problems of Soviet

Card 2/4

SOV/3-59-4-16/42

To Develop Research in the Field of Political Economy

economics, whose development becomes particularly urgent. A mere enumeration of the problems confronting the scientist-economists shows the broad prospects of research work which are open before the chairs of political economy. The author emphasizes the necessity to improve the scientific work of the Chairs and to intensify the supervision on the part of the vuz directors and the Upravleniye prepodavaniya obshchestvennykh nauk (Administration for Teaching Social Sciences). Referring to the remuneration paid by the publishing offices, the author is at a loss to understand why only work which is not provided for by the plan is being paid, while work carried out in accordance with individual plans is not being paid for. He suggests that work performed according to the Chair plan over and above the established minimum be paid. In this connection reference is made to the scientific workers of the Institut ekonomiki AN SSSR (Institute of Economics AS USSR). Dealing with the theses for Doctors' degrees that are being prepared in the Leningrad vuzes this year, the author mentions Docent N.D. Kolesov of Leningrad University, Docent I.D.

Card 3/4

SOV/3-59-4-16/42

Develop Research in the Field of Political Economy

Denisenko of the Leningradskiy tekstil'nyy institut (Leningrad Textile Institute), Docent B.I. Kudryavtsev of the Leningradskiy institut inzhenerov zheleznodorozhnogo transporta (Leningrad Institute of RR Engineers). The author further mentions the Permskiy universitet (Perm' University), Leningradskiy mekhanicheskiy institut (Leningrad Mechanical Institute), Saratovskiy universitet (Saratov University), Ural'skiy universitet (Ural University), Professor N.A. Tsagolov of Moscow University, Professor A.F. Yakovlev of the Moskovskiy gosudarstvennyy ekonomicheskiy institut (Moscow State Institute of Economics), Doctor of Economic Sciences M.S. Atlas of the Moskovskiy finansovyy institut (Moscow Finance Institute), Professor N.K. Karatayev of the Institute of Economics AS USSR, and Rostov University.

Card 4/4

BROVER, Izrail' Moiseyevich, prof., doktor ekonom. nauk; BOBKOV, Karl Illarionovich, kand. ekonom.nauk, dots.; BORISOV, Yevgeniy Filipovich, kand. ekonom.nauk; MATSUK, R.V., red.; GRIGORCHUK, L.A., tekhn. red.

[A reader on economics; socialist production methods] Khrestomatiia po politicheskoi ekonomii; sotsialisticheskii sposob proizvodstva. Moskva, Gos.izd-vo "Vysshaya shkola," 1961. 412 p.
(MIRA 14:12)

(Economics)

BOBKOV, K.

For the aid of those who study Lenin's legacy in the field of economic theory (V.I. Lenin's development of the Marxist theory of the reproduction of communal capital in the struggle against liberal Populists and "legal" Marxists" by I. M. Mrachkovskaia. Reviewed by K.Bobkov). Vop.ekon. no.4:97-100 Ap '61. (MIRA 14:3)
(Lenin Vladimir Il'ich, 1870-1924)
(Mrachkovskaia, I.M.)

БОБРОВ, К.

Research conducted by the economics departments of institutions
of higher learning. Vop. ekon. no.2:150-155 F '62. (MIRA 15:1)
(Economic research)

AL'TER, L.B., doktor ekon. nauk; BLYUMIN, I.G., doktor ekon. nauk
[deceased]; KARATAYEV, N.K., prof.; REUEL', A.L., doktor
ekon. nauk; STEPANOV, I.G., doktor ekon. nauk; SHTEYN, V.M.,
doktor ekon. nauk; POLYANSKIY, F.Ya., doktorist. nauk;
BOBKOV, K.I., kand. ekon. nauk; VASILEVSKIY, Ye.G., kand.
ekon. nauk; MOROZOV, F.M., kand. ekon. nauk; PONOMAREV, Ye.I.,
kand. ekon. nauk; RYNDINA, M.N., kand. ekon. nauk; FIRSOVA, S.M.,
kand. ekon. nauk; TSAGA, V.F., kand. ekon. nauk; ZHUK, I., red.;
VOSKRESENSKAYA, T., red.; NEZNANOV, V., red.; ULANOVA, L., tekhn.
red.

[History of economic theories] Istorii ekonomicheskikh uchenii.
Moskva, Sotsekgiz, 1963. 549 p. (MIRA 17:2)

1. Akademiya nauk SSSR. Institut ekonomiki.

BOBKOV, K.N., agronom; SHIKULA, N.K., kand.sel'skokhoz. nauk

State farm improves soil fertility. Zemledelie 25 no.10:14-21
0 '63. (MIRA 16:11)

1. Ukrainskiy nauchno-issledovatel'skiy institut pochvovedeniya
imeni A.N. Sokolovskogo.

ITSKOVICH, G.M.; KISELEV, V.A.; CHERNAVSKIY, S.A.; BOBKOV, K.N.;
PANICH, B.B.; BAZHENOV, D.V., red.

[Preparation of a course project on machine parts; reference
manual] Kursovoe proektirovanie detalei mashin; uchebno-
spravochnoe posobie. Izd.4., perer. Moskva, Mashinostroenie
1964. 594 p. (MIRA 18:5)

BOBKOV, L. Armaturshchik

My suggestions. Stroitel' no.4:14 Ap '59.
(Reinforced concrete)

(MIRA 12:6)

ABRAMOV, A.S.; MENDEL'SON, V.S.; FREYDIN, G.Yu.; POGOREL'SKIY, M.A.;
BOEKOV, L.I.; SELEKH, V.F.

Designing die casting molds for diamond tools. Mashinostroitel'
no.11:30-32 N '64 (MIRA 18:2)

BOBKOV, L.S.

Automobile surface preparation prior to painting. Lakokras.mat.
i ikh prim. no.2:75-76 '60. (MIRA 14:4)

1. Iz opyta raboty Moskovskogo avtozavoda imeni I.A.Likhaheva.
(Automobiles--Painting)

S/032/60/026/04/30/046
B010/B006

AUTHOR: Bobkov, L.S.

TITLE: On the Method of Testing the Impact Strength of Varnish Coats

PERIODICAL: Zavodskaya laboratoriya, 1960, Vol. 26, No. 4, pp. 489-490

TEXT: Questions concerning impact destruction of varnish coats by various devices are discussed. This test method is laid down in GOST 4765-49 (instead of OST 10086-39) and consists in measuring the drop height of a striker weighing 1 kg required to destroy the varnish coat (and/or the maximum height before occurrence of destruction). For this test, a device was designed at the Nauchno-issledovatel'skiy institut lakov i krasok (NILK) (Scientific Research Institute of Varnishes and Paints). Since it has several drawbacks, a second device of the type U-1^A was designed. With the latter however, the varnish coat separates at the point of impact of the striker, especially in the case of multilayer coatings. A device of the type U-2^B in which the striker is a ball of larger diameter than in the U-1 device was designed at the Institut GIPI-4 (Institute GIPI-4). Indentations produced by the three above-

Card 1/2

On the Method of Testing the Impact Strength
of Varnish Coats

S/032/60/026/04/30/046
B010/B006

mentioned devices in metals serving as varnish foundations, as observed after the tests, are shown in drawings (Fig. 1). A comparison (Table) of the test results of various varnish samples obtained by means of the three devices shows that the U-2 device gives considerably higher values. It is recommended not to use the U-2 device, because the values obtained by it are distorted. Since the varnish coat separates in tests with the U-1 device it is recommended to develop a new and more suitable device basing on the one designed at the NILK. A publication by S.V. Yakubovich is mentioned in the paper. There are 1 figure, 1 table, and 1 Soviet reference. (V)

ASSOCIATION: Moskovskiy avtozavod im. Likhacheva (Moscow Automobile Plant
imeni Likhachev)

Card 2/2

BOBKOV, I.S.; DANILOVA, G.F.

Painting of bicycle parts in a conveyor. Lakokras.mat.i ikh prim.
no.l:67-70 '61. (MIRA 14:4)

1. Iz opyta raboty Moskovskogo avtozavoda imeni I.A.Likhacheva.
(Bicycles and tricycles--Painting)

BOBKOV, L.S.

Mechanization of painting operations at the Likachev Automobile
Plant. Mashinostroitel' no.5:18-19 My '61. (MIRA 14:5)
(Moscow--Motor vehicles--Painting)

BOBKOV, L.S.; DANILOVA, G.F.

Painting of motorbuses in the I.A. Likhachev Automobile Plant.
Lakokras.mat.i ikh prim. no.3:83-84 '62. (MIRA 15:7)
(Motorbuses--Painting)

BOBKOV, L.S.

Equipment for spray painting in the electric field manufactured
in the Hungarian People's Republic. Lakokras. mat. i ikh prom.
no.5:62-64 '63. (MIRA 16:11)

ZIL'BERBERG, V.I.; ROZNO, L.I.; GULYAYEV, A.I.; TSYRLIN, M.I.;
BOBKOV, L.S., inzh., retsenzent; MANUYKOV, P.H., inzh.,
red.

[Overall mechanization and automation of painting operations] Kompleksnaia mekhanizatsiia i' avtomatizatsiia okrasochnykh robot. Moskva, Mashinostroenie, 1965. 146 p.
(MIRA 18:6)

L 7007-65 EWT(1)/EWA(h) Feb AFWL/SSD/AFSTR GW

ACCESSION NR: AP4045787 S/0049/64/000/009/1360/1375

AUTHOR: Fedotov, B. A.; Kuzin, I. P.; Bobkov, M. F.

TITLE: Detailed seismological investigations at Kamchatka in 1961 and 1962

SOURCE: AN SSSR. Izvestiya. Seriya geofizicheskaya, no. 9, 1964, 1360-1375

TOPIC TAGS: seismic activity, seismological station, Pacific seismic Belt, seismography, Kamchatka

ABSTRACT: The results of observations made at a network of seismic stations established by a special Pacific seismic expedition to Kamchatka during the period 1961-1962 are reviewed. The instruments, methods, and techniques of observation and data reduction were essentially the same as those used in an earlier expedition to the Kurile Islands from 1958 to 1962. It has been experimentally established that near-earthquakes with $K > 10$ are clearly recorded at distances of 200-300 km. On the basis of the seismic materials gathered during the first year at Kamchatka, it was possible to compile a map of epi-

Card 1/3

L 7007-65

ACCESSION NR: AP4045787

centers, a map of seismic activity (based on earthquakes with foci depths of less than 60 km), a compound vertical section, and a frequency diagram. A distinct earthquake belt was identified running parallel to the deep-water depression through the tips of the Kronotskiy and Shipunskiy peninsulas southwest to the 52° latitude line. The compound vertical section shows that this belt is an outcrop of the Pacific focal zone which crosses the deep-water depression and the elevated Kamchatka. The belt reflects the intensive contemporary processes taking place in the earth's mantle which led to the development of the island arc and the deep-water depression. The map of epicenters indicates that the deep-water depression, the structure of the Shipunskiy peninsula and its underwater extension, and the depression of the Kamchatka River and bordering mountains continue to develop intensively today. Corrections will have to be made in the map of seismic zoning of Kamchatka. On the eastern shore of Kamchatka the nine-point intensity zone should be expanded to include the town of Petropavlovsk-Kamchatskiy. Orig. art. has: 8 figures and 2 tables.

ASSOCIATION: Akademiya nauk SSSR, Institut fiziki Zemli (Academy of Sciences SSSR, Institute of Physics of the Earth); Sibirskoye otde-

Card 2/3

L 7007-65

ACCESSION NR: AP404787

leniye, Institut vulkanologii (Siberian Department, Institute of
Vulcanology)

SUBMITTED: 26Jul63

ATD PRESS: 3103

ENCL: 00

SUB CODE: ES

NO REF SOV: 029

OTHER: 004

Card 3/3

BOBKOV, M. I.

Fuel Abstracts
June 1954
Steam Raising and
Steam Engines

③
4565. IMPROVING ECONOMY OF BOILER PLANT OPERATING ON PULVERIZED
ANTHRACITE DUFF. Bobkov, M. I., Trignont, V.D. and Sukhov, A.I.
(Energetik (Pur Engr. Moscow) Dec. 1953, 4-7). Modifications and
subsequent performance of the 120-150 tons/h boiler, mentioned in Fuel Abstr.,
1954, vol. 15, 503, are described.

BOBKOV, M. I.

524N/5
735.9
.B6

Opyt Ekspluatatsii Zuyevskoy GRES (Operational Experience of the State Regional
Electrical Power Stations of Zuyevka, by) M. I. Bobkov (I Dr.) Pod Obshchey Red.
P. R. Sizin. Moskva, Gosenergoizdat, 1954.

247 P. Illus., Diagr., Tables.

LONSKIY, Ye.D.; STROMSKIY, P.P.; BOBKOV, M.M.

~~SECRET~~
Highly productive equipment for pneumatic flux feeding. Elek.1
tepl.tiaga 3 no.6:10-11 Je '59. (MIRA 12:9)
(Car wheels--Welding) (Pneumatic machinery)

BOBKOV, N. A.

BOBKOV, N.A.; KAZITSYN, Yu.V.

Spinels of southern Yakutia. Zap. Vses. min. ob-va 83 no. 2:163-167 '54.

(Yakutia--Spinel group) (Spinel group--Yakutia) (MLRA 7:7)

BOEKOV, N.G.

Comparative evaluation of collectors. TSvet. met. 37 no.9:12 3 '64.
(MIRA 18:7)

BOBKOV, N. K.

"Dynamics of the Processes of Soil Formation of Turf-Podzolic Soils Built up Over Thick Ancient Alluvial Sands Under Pine Seedlings." Cand Agr Sci, Inst of Socialized Agriculture, Minsk, 1954. (RZhBiol, No 8, Apr 55)

SO: Sum. No. 704, 2 Nov 55 - Survey of Scientific and Technical Dissertations Defended at USSR Higher Educational Institutions (16).

BOBKOV, N.K., kand. sel'khoz. nauk

[Characteristics of turf-Podzolic soils in deep ancient alluvial sands; reports at the conference on methods and research on the increase of fertility and productivity of light soils] Osobennosti dernovo-podzolistykh pochv na glubokikh drevnealluvial'nykh peskakh; doklad na nauchno-metodicheskom soveshchani po povysheniiu plodorodiia i proizvoditel'nosti legkikh pochv. Minsk, Akad.sel'khoz.nauk BSSR, 1959. 14 p.
(MIRA 17:4)

BOBKOV, N.K.

USSR/Forestry - Forest Management.

K-4

Abs Jour : Ref Zhur - Biol., No 5, 1958, 20139

Author : Moiseyenko, F.P., Bobkov, N.K.

Inst : -

Title : Forest Renewal Felling in Soil Protection Forests.

Orig Pub : Sb. rabot po lesn. kh-vu Ml.-Ll, Goslesbumizdat, 1957, 21-25.

Abstract : A study has been made of the porosity, water permeability and consistence of the forest soils in the dry pine wood stands of differing ages and compactness. Data is presented on the changes with age in the output of commercial wood and saw logs, while natural renewal in various forest types is characterized. On the baiss of the researched data the authors come to the conclusion that the protective features of the arid pine wood appear stronger in the ages from 50-60 to 110-130 years. The recommended age for

Card 1/2

USSR/Forestry - Forest Management.

K-4

Abs Jour : Ref Zhur - Biol., No 5, 1958, 20139

cutting is 101-120 years, the felling method is by dense forest cutting with cultivation of the clearings.

Card 2/2

- 40 -

~~BOBKOV, N.M., red.;~~ GIRICHEV, S.N., red.; TOSHCHÉVIKOV, V.P., red.;
BOBKOV, B.V., red.; YEMEL'YANOVA, I., red.; DAVLETOV, Kh.,
tekhn.red.

[Technical education in Kazakh schools; a collection of articles]
Politekhnicheskoe obuchenie v shkolakh Kazakhskoi SSR: sbornik
statei. Alma-Ata, Kazakhskoe gos. uchebno-pedagog. izd-vo.
Pt.1. 1957. 195 p. (MIRA 11:5)

1. Kazakh S.S.R. Upravleniye shkol.
(Kazakhstan--Technical education)

BOIKOV, N. P.

27074 BOIKOV, N. P., MIKHAYLOVSKIY, Yu. V., RYZHKOV, A. N., TSVETKOV, B. S.
Mekhanizatsiya trudoyemkikh i tyazhelykh rabot, 1949, No.8, s. 32-36.

SO: Letopis' Zhurnal'nykh Statey, Vol. 36, 1949

131 AND 130 SERIES PROCESSES AND PROPERTIES INDEX 130 AND 129 SERIES

Bobkov, N. P.

857. TANINIS (MOBILE) GAS PRODUCERS FOR RAW FIREWOOD AND WASTE PRODUCTS OF TIMBER FELLING. Bobkov, N. P., Mikhailovskii, Yu. V., Ryshkov, A. N. and Tsvetkov, B. S. (*Zh. Ek. Topliva (Fuel Econ.)*, Nov. 1950, 24-27).

A

An illustrated description and engine performance figures are given for a new type of gas producer for use with tractors, lorries and generating sets. It uses small logs 450-500 m.m. long by 20-100 m.m. diam. with moisture up to 100% abs., and compares favourably with existing types running on specially prepared and dried wood blocks. The producer is 1850 m.m. high, rectangular in section, and the top half, which serves as a fuel hopper, measure 550 by 400 m.m. Cold air is delivered by a blower at 350 m.m. head of water to 16 nozzles surrounding the combustion zone and inclined upwards at 30° to the horizontal. There is a throttled outlet in the lid at the top of the fuel hopper. If the wood is dry enough, this outlet is closed and the producer functions as a normal down-draught type. With wet wood

ASA, SLA METALLURGICAL LITERATURE CLASSIFICATION

XSON BOWIEV XSON BOWIEV

XSON BOWIEV XSON BOWIEV

XSON BOWIEV XSON BOWIEV

BEKOV, N.M.; NEKIYULOVA, K.S.

Member of a scientific organization of the work. Fed. dep. 110000.
47 no.8:50-51 Ag 165. (MIRA 1945)

1. Zamestitel' nachalnika informatsionnogo depa Kanalin Yugo-Zapadnoy
dorogi (for Bekov). 2. Staryiy izh.-ekonomist depa Kanalin Yugo-
Zapadnoy dorogi (for Nekiyulova).

SKLYAR, V.A.; AVRAMENKO, K.P.; PAVLOV, D.F.; BOBKOV, N.V.; BERESTOVAYA, R.V.;
SKRYPNIK, Ye.P.; SEMONENKO, Ye.T.; SERGEYEVA, V.P.; KOLYAKO, D.A.,
red.; SOLDATOVA, N.P., otvetstv.za vypusk; GRISHNYAYEV, B.G.,
tekhn.red.

[Economy of Krasnodar Territory; a statistical manual] Narodnoe
khoziaistvo Krasnodarskogo kraia; statisticheski sbornik.
Krasnodar, Gosstatizdat, 1958. 233 p. (MIRA 12:2)

1. Krasnodarskiy kray. Statisticheskoye upravleniye. 2. Nachal'nik
Krasnodarskogo krayevogo statisticheskogo upravleniya (for Kolyako).
(Krasnodar Territory--Statistics)

BOBKOV, Nikolay Vladimirovich; GUREVICH, Sh.M., dots., kand. ekon.
nauk, retsenzent; KOVALEV, A.I., retsenzent; MYASHNIKOV,
N.V., ~~ret.~~

[General course in river transportation] Obshchii kurs
rechnogo transporta. Moskva, "Transport," 1964. 212 p.
(MIRA 17:4)

PROCEDURES AND PROPERTIES INDEX

16

ca

Polarimetric determination of the carbohydrate content of intermediate products in the production of alcohol from potatoes. *E. Lobkovsky, Spisokovya Prom. 13, No. 12, 63-64 (1936); Chem. Zentr. 1937, 1, 4876.*—The detn. of starch in potatoes: 100 g. of potato mash is treated with malt glycerol ext., dild. to 500 cc. with water, and 20 cc. of the filtrate boiled 1 hr. 45 min. with 40 cc. 10% HCl and 20 cc. water. After cooling, clarifying and filtering, the soln. is examd. with the polariscope. Starch is detd. in malt in an analogous manner. For the detn. of carbohydrates in the intermediate products, 20 g. of the filtrate from the mash, etc., is treated with 40 cc. of 10% HCl and the detn. completed as above. M. G. Moore

ASB.S.L.A. METALLURGICAL LITERATURE CLASSIFICATION

FROM SOURCE

FROM SOURCE

PROCESSING AND PROPERTIES INDEX

16

ca

The storage of potatoes in silos and their processing to yield alcohol. F. K. Bobkov. *Spiro-Veduchnaya Prom.* 6 15, No. 6, 8-13 (1938); *Chem. Zentr.* 1938, II, 3173; cf. C. A. 33, 4720, 7953. Several years' observations have shown that when whole potatoes are stored in pits the starch loss is about 10 times greater than when the potato pulp is stored in silos. In the latter case various organic acids are formed; these acids together with the simultaneous exclusion of air afford protection against bacteria and mold fungi. By the fermentation of potato pulp so stored, alc. is obtained which has only a slightly acrid odor. Processing of the pulp is simplified if H₂SO₄ is added during storage. M. G. Moore

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

GROUP	CLASS	SECTION	SUBSECTION	ALPHABETIC	ALPHABETIC
1	2	3	4	5	6

PROCESSUS AND PROPERTIES INDEX

16

ca

Sorghum stems as a raw material for the production of natural rum. P. Bohkov. *Spirito-podochuaya Prosa*. 13, No. 8, 33-6(1938); *Chemie industrie* 41, 1179.—Worts obtained from sorghum stems can be used for the production of natural rum. The esters formed during the fermentation of these worts resemble in aroma the esters of the head fraction of natural rum obtained from the Jamaica sugar cane. A. Papineau-Couture

ASS-51A METALLURGICAL LITERATURE CLASSIFICATION

E-2740000

1937 AND 1938 GROUPS

190 AND 191 GROUPS

192 AND 193 GROUPS

194 AND 195 GROUPS

196 AND 197 GROUPS

198 AND 199 GROUPS

200 AND 201 GROUPS

202 AND 203 GROUPS

204 AND 205 GROUPS

206 AND 207 GROUPS

208 AND 209 GROUPS

210 AND 211 GROUPS

212 AND 213 GROUPS

214 AND 215 GROUPS

216 AND 217 GROUPS

218 AND 219 GROUPS

220 AND 221 GROUPS

222 AND 223 GROUPS

224 AND 225 GROUPS

226 AND 227 GROUPS

228 AND 229 GROUPS

230 AND 231 GROUPS

232 AND 233 GROUPS

234 AND 235 GROUPS

236 AND 237 GROUPS

238 AND 239 GROUPS

240 AND 241 GROUPS

242 AND 243 GROUPS

244 AND 245 GROUPS

246 AND 247 GROUPS

248 AND 249 GROUPS

250 AND 251 GROUPS

252 AND 253 GROUPS

254 AND 255 GROUPS

256 AND 257 GROUPS

258 AND 259 GROUPS

260 AND 261 GROUPS

262 AND 263 GROUPS

264 AND 265 GROUPS

266 AND 267 GROUPS

268 AND 269 GROUPS

270 AND 271 GROUPS

272 AND 273 GROUPS

274 AND 275 GROUPS

276 AND 277 GROUPS

278 AND 279 GROUPS

280 AND 281 GROUPS

282 AND 283 GROUPS

284 AND 285 GROUPS

286 AND 287 GROUPS

288 AND 289 GROUPS

290 AND 291 GROUPS

292 AND 293 GROUPS

294 AND 295 GROUPS

296 AND 297 GROUPS

298 AND 299 GROUPS

300 AND 301 GROUPS

302 AND 303 GROUPS

304 AND 305 GROUPS

306 AND 307 GROUPS

308 AND 309 GROUPS

310 AND 311 GROUPS

312 AND 313 GROUPS

314 AND 315 GROUPS

316 AND 317 GROUPS

318 AND 319 GROUPS

320 AND 321 GROUPS

322 AND 323 GROUPS

324 AND 325 GROUPS

326 AND 327 GROUPS

328 AND 329 GROUPS

330 AND 331 GROUPS

332 AND 333 GROUPS

334 AND 335 GROUPS

336 AND 337 GROUPS

338 AND 339 GROUPS

340 AND 341 GROUPS

342 AND 343 GROUPS

344 AND 345 GROUPS

346 AND 347 GROUPS

348 AND 349 GROUPS

350 AND 351 GROUPS

352 AND 353 GROUPS

354 AND 355 GROUPS

356 AND 357 GROUPS

358 AND 359 GROUPS

360 AND 361 GROUPS

362 AND 363 GROUPS

364 AND 365 GROUPS

366 AND 367 GROUPS

368 AND 369 GROUPS

370 AND 371 GROUPS

372 AND 373 GROUPS

374 AND 375 GROUPS

376 AND 377 GROUPS

378 AND 379 GROUPS

380 AND 381 GROUPS

382 AND 383 GROUPS

384 AND 385 GROUPS

386 AND 387 GROUPS

388 AND 389 GROUPS

390 AND 391 GROUPS

392 AND 393 GROUPS

394 AND 395 GROUPS

396 AND 397 GROUPS

398 AND 399 GROUPS

400 AND 401 GROUPS

402 AND 403 GROUPS

404 AND 405 GROUPS

406 AND 407 GROUPS

408 AND 409 GROUPS

410 AND 411 GROUPS

412 AND 413 GROUPS

414 AND 415 GROUPS

416 AND 417 GROUPS

418 AND 419 GROUPS

420 AND 421 GROUPS

422 AND 423 GROUPS

424 AND 425 GROUPS

426 AND 427 GROUPS

428 AND 429 GROUPS

430 AND 431 GROUPS

432 AND 433 GROUPS

434 AND 435 GROUPS

436 AND 437 GROUPS

438 AND 439 GROUPS

440 AND 441 GROUPS

442 AND 443 GROUPS

444 AND 445 GROUPS

446 AND 447 GROUPS

448 AND 449 GROUPS

450 AND 451 GROUPS

452 AND 453 GROUPS

454 AND 455 GROUPS

456 AND 457 GROUPS

458 AND 459 GROUPS

460 AND 461 GROUPS

462 AND 463 GROUPS

464 AND 465 GROUPS

466 AND 467 GROUPS

468 AND 469 GROUPS

470 AND 471 GROUPS

472 AND 473 GROUPS

474 AND 475 GROUPS

476 AND 477 GROUPS

478 AND 479 GROUPS

480 AND 481 GROUPS

482 AND 483 GROUPS

484 AND 485 GROUPS

486 AND 487 GROUPS

488 AND 489 GROUPS

490 AND 491 GROUPS

492 AND 493 GROUPS

494 AND 495 GROUPS

496 AND 497 GROUPS

498 AND 499 GROUPS

500 AND 501 GROUPS

502 AND 503 GROUPS

504 AND 505 GROUPS

506 AND 507 GROUPS

508 AND 509 GROUPS

510 AND 511 GROUPS

512 AND 513 GROUPS

514 AND 515 GROUPS

516 AND 517 GROUPS

518 AND 519 GROUPS

520 AND 521 GROUPS

522 AND 523 GROUPS

524 AND 525 GROUPS

526 AND 527 GROUPS

528 AND 529 GROUPS

530 AND 531 GROUPS

532 AND 533 GROUPS

534 AND 535 GROUPS

536 AND 537 GROUPS

538 AND 539 GROUPS

540 AND 541 GROUPS

542 AND 543 GROUPS

544 AND 545 GROUPS

546 AND 547 GROUPS

548 AND 549 GROUPS

550 AND 551 GROUPS

552 AND 553 GROUPS

554 AND 555 GROUPS

556 AND 557 GROUPS

558 AND 559 GROUPS

560 AND 561 GROUPS

562 AND 563 GROUPS

564 AND 565 GROUPS

566 AND 567 GROUPS

568 AND 569 GROUPS

570 AND 571 GROUPS

572 AND 573 GROUPS

574 AND 575 GROUPS

576 AND 577 GROUPS

578 AND 579 GROUPS

580 AND 581 GROUPS

582 AND 583 GROUPS

584 AND 585 GROUPS

586 AND 587 GROUPS

588 AND 589 GROUPS

590 AND 591 GROUPS

592 AND 593 GROUPS

594 AND 595 GROUPS

596 AND 597 GROUPS

598 AND 599 GROUPS

600 AND 601 GROUPS

602 AND 603 GROUPS

604 AND 605 GROUPS

606 AND 607 GROUPS

608 AND 609 GROUPS

610 AND 611 GROUPS

612 AND 613 GROUPS

614 AND 615 GROUPS

616 AND 617 GROUPS

618 AND 619 GROUPS

620 AND 621 GROUPS

622 AND 623 GROUPS

624 AND 625 GROUPS

626 AND 627 GROUPS

628 AND 629 GROUPS

630 AND 631 GROUPS

632 AND 633 GROUPS

634 AND 635 GROUPS

636 AND 637 GROUPS

638 AND 639 GROUPS

640 AND 641 GROUPS

642 AND 643 GROUPS

644 AND 645 GROUPS

646 AND 647 GROUPS

648 AND 649 GROUPS

650 AND 651 GROUPS

652 AND 653 GROUPS

654 AND 655 GROUPS

656 AND 657 GROUPS

658 AND 659 GROUPS

660 AND 661 GROUPS

662 AND 663 GROUPS

664 AND 665 GROUPS

666 AND 667 GROUPS

668 AND 669 GROUPS

670 AND 671 GROUPS

672 AND 673 GROUPS

674 AND 675 GROUPS

676 AND 677 GROUPS

678 AND 679 GROUPS

680 AND 681 GROUPS

682 AND 683 GROUPS

684 AND 685 GROUPS

686 AND 687 GROUPS

688 AND 689 GROUPS

690 AND 691 GROUPS

692 AND 693 GROUPS

694 AND 695 GROUPS

696 AND 697 GROUPS

698 AND 699 GROUPS

700 AND 701 GROUPS

702 AND 703 GROUPS

704 AND 705 GROUPS

706 AND 707 GROUPS

708 AND 709 GROUPS

710 AND 711 GROUPS

712 AND 713 GROUPS

714 AND 715 GROUPS

716 AND 717 GROUPS

718 AND 719 GROUPS

720 AND 721 GROUPS

722 AND 723 GROUPS

724 AND 725 GROUPS

726 AND 727 GROUPS

728 AND 729 GROUPS

730 AND 731 GROUPS

732 AND 733 GROUPS

734 AND 735 GROUPS

736 AND 737 GROUPS

738 AND 739 GROUPS

740 AND 741 GROUPS

742 AND 743 GROUPS

744 AND 745 GROUPS

746 AND 747 GROUPS

748 AND 749 GROUPS

750 AND 751 GROUPS

752 AND 753 GROUPS

754 AND 755 GROUPS

756 AND 757 GROUPS

758 AND 759 GROUPS

760 AND 761 GROUPS

762 AND 763 GROUPS

764 AND 765 GROUPS

766 AND 767 GROUPS

768 AND 769 GROUPS

770 AND 771 GROUPS

772 AND 773 GROUPS

774 AND 775 GROUPS

776 AND 777 GROUPS

778 AND 779 GROUPS

780 AND 781 GROUPS

782 AND 783 GROUPS

784 AND 785 GROUPS

786 AND 787 GROUPS

788 AND 789 GROUPS

790 AND 791 GROUPS

792 AND 793 GROUPS

794 AND 795 GROUPS

796 AND 797 GROUPS

798 AND 799 GROUPS

800 AND 801 GROUPS

802 AND 803 GROUPS

804 AND 805 GROUPS

806 AND 807 GROUPS

808 AND 809 GROUPS

810 AND 811 GROUPS

812 AND 813 GROUPS

814 AND 815 GROUPS

816 AND 817 GROUPS

818 AND 819 GROUPS

820 AND 821 GROUPS

822 AND 823 GROUPS

824 AND 825 GROUPS

826 AND 827 GROUPS

828 AND 829 GROUPS

830 AND 831 GROUPS

832 AND 833 GROUPS

834 AND 835 GROUPS

836 AND 837 GROUPS

838 AND 839 GROUPS

840 AND 841 GROUPS

842 AND 843 GROUPS

844 AND 845 GROUPS

846 AND 847 GROUPS

848 AND 849 GROUPS

850 AND 851 GROUPS

852 AND 853 GROUPS

854 AND 855 GROUPS

856 AND 857 GROUPS

858 AND 859 GROUPS

860 AND 861 GROUPS

862 AND 863 GROUPS

864 AND 865 GROUPS

866 AND 867 GROUPS

868 AND 869 GROUPS

870 AND 871 GROUPS

872 AND 873 GROUPS

874 AND 875 GROUPS

876 AND 877 GROUPS

878 AND 879 GROUPS

880 AND 881 GROUPS

882 AND 883 GROUPS

884 AND 885 GROUPS

886 AND 887 GROUPS

888 AND 889 GROUPS

890 AND 891 GROUPS

892 AND 893 GROUPS

894 AND 895 GROUPS

896 AND 897 GROUPS

898 AND 899 GROUPS

900 AND 901 GROUPS

902 AND 903 GROUPS

904 AND 905 GROUPS

906 AND 907 GROUPS

908 AND 909 GROUPS

910 AND 911 GROUPS

912 AND 913 GROUPS

914 AND 915 GROUPS

916 AND 917 GROUPS

918 AND 919 GROUPS

920 AND 921 GROUPS

922 AND 923 GROUPS

924 AND 925 GROUPS

926 AND 927 GROUPS

928 AND 929 GROUPS

930 AND 931 GROUPS

932 AND 933 GROUPS

934 AND 935 GROUPS

936 AND 937 GROUPS

938 AND 939 GROUPS

940 AND 941 GROUPS

942 AND 943 GROUPS

944 AND 945 GROUPS

946 AND 947 GROUPS

948 AND 949 GROUPS

950 AND 951 GROUPS

952 AND 953 GROUPS

954 AND 955 GROUPS

956 AND 957 GROUPS

958 AND 959 GROUPS

960 AND 961 GROUPS

962 AND 963 GROUPS

964 AND 965 GROUPS

966 AND 967 GROUPS

968 AND 969 GROUPS

970 AND 971 GROUPS

972 AND 973 GROUPS

974 AND 975 GROUPS

976 AND 977 GROUPS

978 AND 979 GROUPS

980 AND 981 GROUPS

982 AND 983 GROUPS

984 AND 985 GROUPS

986 AND 987 GROUPS

988 AND 989 GROUPS

990 AND 991 GROUPS

992 AND 993 GROUPS

994 AND 995 GROUPS

996 AND 997 GROUPS

998 AND 999 GROUPS

1000 AND 1001 GROUPS

1002 AND 1003 GROUPS

1004 AND 1005 GROUPS

1006 AND 1007 GROUPS

1008 AND 1009 GROUPS

1010 AND 1011 GROUPS

1012 AND 1013 GROUPS

1014 AND 1015 GROUPS

1016 AND 1017 GROUPS

1018 AND 1019 GROUPS

1020 AND 1021 GROUPS

1022 AND 1023 GROUPS

1024 AND 1025 GROUPS

1026 AND 1027 GROUPS

1028 AND 1029 GROUPS

1030 AND 1031 GROUPS

1032 AND 1033 GROUPS

1034 AND 1035 GROUPS

1036 AND 1037 GROUPS

1038 AND 1039 GROUPS

1040 AND 1041 GROUPS

1042 AND 1043 GROUPS

1044 AND 1045 GROUPS

1046 AND 1047 GROUPS

1048 AND 1049 GROUPS

1050 AND 1051 GROUPS

1052 AND 1053 GROUPS

1054 AND 1055 GROUPS

1056 AND 1057 GROUPS

1058 AND 1059 GROUPS

1060 AND 1061 GROUPS

1062 AND 1063 GROUPS

1064 AND 1065 GROUPS

1066 AND 1067 GROUPS

1068 AND 1069 GROUPS

1070 AND 1071 GROUPS

1072 AND 1073 GROUPS

1074 AND 1075 GROUPS

1076 AND 1077 GROUPS

1078 AND 1079 GROUPS

1080 AND 1081 GROUPS

1082 AND 1083 GROUPS

1084 AND 1085 GROUPS

1086 AND 1087 GROUPS

1088 AND 1089 GROUPS

1090 AND 1091 GROUPS

1092 AND 1093 GROUPS

1094 AND 1095 GROUPS

1096 AND 1097 GROUPS

1098 AND 1099 GROUPS

1100 AND 1101 GROUPS

1102 AND 1103 GROUPS

1104 AND 1105 GROUPS

1106 AND 1107 GROUPS

1108 AND 1109 GROUPS

1110 AND 1111 GROUPS

1112 AND 1113 GROUPS

1114 AND 1115 GROUPS

1116 AND 1117 GROUPS

1118 AND 1119 GROUPS

1120 AND 1121 GROUPS

1122 AND 1123 GROUPS

1124 AND 1125 GROUPS

1126 AND 1127 GROUPS

1128 AND 1129 GROUPS

1130 AND 1131 GROUPS

1132 AND 1133 GROUPS

1134 AND 1135 GROUPS

1136 AND 1137 GROUPS

1138 AND 1139 GROUPS

1140 AND 1141 GROUPS

1142 AND 1143 GROUPS

1144 AND 1145 GROUPS

1146 AND 1147 GROUPS

1148 AND 1149 GROUPS

1150 AND 1151 GROUPS

1152 AND 1153 GROUPS

1154 AND 1155 GROUPS

1156 AND 1157 GROUPS

1158 AND 1159 GROUPS

1160 AND 1161 GROUPS

1162 AND 1163 GROUPS

1164 AND 1165 GROUPS

1166 AND 1167 GROUPS

1168 AND 1169 GROUPS

1170 AND 1171 GROUPS

1172 AND 1173 GROUPS

1174 AND 1175 GROUPS

1176 AND 1177 GROUPS

1178 AND 1179 GROUPS

1180 AND 1181 GROUPS

1182 AND 1183 GROUPS

1184 AND 1185 GROUPS

1186 AND 1187 GROUPS

1188 AND 1189 GROUPS

1190 AND 1191 GROUPS

1192 AND 1193 GROUPS

1194 AND 1195 GROUPS

1196 AND 1197 GROUPS

1198 AND 1199 GROUPS

1200 AND 1201 GROUPS

1202 AND 1203 GROUPS

1204 AND 1205 GROUPS

1206 AND 1207 GROUPS

1208 AND 1209 GROUPS

1210 AND 1211 GROUPS

1212 AND 1213 GROUPS

1214 AND 1215 GROUPS

1216 AND 1217 GROUPS

1218 AND 1219 GROUPS

1220 AND 1221 GROUPS

1222 AND 1223 GROUPS

1224 AND 1225 GROUPS

1226 AND 1227 GROUPS

1228 AND 1229 GROUPS

1230 AND 1231 GROUPS

1232 AND 1233 GROUPS

1234 AND 1235 GROUPS

1236 AND 1237 GROUPS

1238 AND 1239 GROUPS

1240 AND 1241 GROUPS

1242 AND 1243 GROUPS

1244 AND 1245 GROUPS

1246 AND 1247 GROUPS

1248 AND 1249 GROUPS

1250 AND 1251 GROUPS

1252 AND 1253 GROUPS

1254 AND 1255 GROUPS

1256 AND

PROCESS AND PROPERTIES INDEX

30

ca

The production of rubber from the roots of kok-saghyz. P. K. Bobkov. *Kauchuk i Resina* 1939, No. 8, 67-70; *Chem. Zvest.* 1940, 1, 142-3; cf. *C. A.* 34, 4299. The different steps in the processing of kok-saghyz are described: (1) extr. of the latex, (2) sepn. and fermentation of the carbohydrate, (3) preliminary treatment for sepn. of rubber, (4) sepn. of rubber and (5) drying of the rubber. Inadequacies and possible improvements in the process are pointed out. The yield per metric ton of undried roots is 16.5 kg. of rubber hydrocarbons. The product obtained by the leaching process contains 84.5% rubber hydrocarbons, 4.3% insol. substances, 11.2% resin and 1-1.2% ash. The tensile strength is 200-215 kg./sq. cm., the elongation 700-80%, the permanent elongation 18-20% and the Geer coeff. of aging 0.80-0.90.
M. G. Moore

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

1930-1939 1940-1949 1950-1959 1960-1969 1970-1979 1980-1989 1990-1999

PROCESSES AND PROPERTIES INDEX

30

CP


Losses of rubber in the processing of the roots of kok-saghyz. P. K. Bobkov. *Caoutchouc and Rubber* (U. S. S. R.) 1939: No. 12: 27-6. The alkali method of processing the roots of kok-saghyz by centrifuging gives a 75-80% extn. of rubber; the losses are 15-13% in the filtrate, 8-5% in the slimes and 2% in the wash waters. The losses can be reduced by settling the slimes in tanks having conical bottoms and vertical baffles, whereby the liquid is first directed downward under the 1st baffle, then upward over the 2nd baffle and the process is repeated. The rubber is extd. from the slimes by grinding, digestion and centrifuging. These measures should decrease the losses by at least 50-60%. H. Z. Kamich

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

6-27-1939

LITERATURE CLASSIFICATION

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----




BOBKOV, S.

Kamensk Combine of Artificial Fibers prepares for work in a
new way. Sots.trud no.12:123-125 D '58.

(MIRA 13:4)

1. Inshener otдела truda i sarabotnoy platy Upravleniya legkoy
promyshlennosti Rostovskogo sovnarkhoza.
(Rostov--Textile fibers, Synthetic)



BOBKOV, S.S.; KAZARNOVSKAYA, R.Sh.

Some problems in ethylene oxidation. Neftekhimii 1 no.5:661-668
S-O '61. (MIRA 15:2)

(Ethylene oxide)

KOLCHIN, I.K.; BOBKOV, S.S.; MARGOLIS, I.Ya.

Catalytic oxidation and ammoxidation of propylene on bismuth molybdates. *Neftakhimija* 4 no.2:201-307 Apr-ap'64 (KIRA 17:8)

1. Institut khimicheskoy fiziki AN SSSR.

KOLCHIN, I.K.; GAL'PERIN, Ye.L.; BOBKOV, S.S.; MARGOLIS, L.Ya.

Catalytic oxidation and oxidative ammonolysis of propylene on
bismuth tungstate. Neftekhimiiia 5 no.1:111-117 Ja-F '65.
(MIRA 18:5)

KOLCHIN, I.K.; GAL'PERIN, Ye.L.; BOBKOV, S.S.; MARGOLIS, L.Ya.

Bismuth-molybdenum-phosphorus catalysts of oxidation and of
oxidative ammonolysis of propylene. *Kin.i kat.* 6 no.5:878-
883 S-O '65. (MIRA 18:11)

ACC NR: AP7001365 (A) SOURCE CODE: UR/0413/66/000/021/0032/0032

INVENTOR: Gus'kov, A. K.; Bobkov, S. S.; Gribov, A. M.; Kolchin, I. K.; Zhakov, V. A.;
Kovalev, N. I.; Lisunova, M. B.; Sokolova, V. A.; Kuznetsova, S. N.; Butusova, V. A.

ORG: none

TITLE: Preparative method for a catalyst. Class 12, No. 187738

SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 21, 1966, 32

TOPIC TAGS: acrylonitrile, chemical synthesis, catalyst preparation, *catalysis*

ABSTRACT: An Author Certificate has been issued for a preparative method for a catalyst for the synthesis of acrylonitrile by oxidative ammonolysis of propylene. A carrier with improved strength and heat resistance is prepared by molding, drying and heating to 1200—1250 a mixture of Kaolin and α -alumina. The carrier is subsequently impregnated with bismuth, molybdenum, and phosphorus compounds. [B0]

SUB CODE: 07/ SUBM DATE: 01Apr64/. ATD PRESS: 5109

Card. 1/1

UDC: 66.094.373

Bobkov, T. M.

133-10-8/26

AUTHOR: Zabaluyev, I. P., Bobkov, T. M. and Tarashchuk, N. T.

TITLE Smelting of Chromium Nickel Steel Using Pelletised Nickel Oxide. (Vyplavka Khromonikelevoy Stali s Primeneniyem Okomkovannoy Zakisi Nikelya).

PERIODICAL: Stal', 1957, No.10, pp. 899-901 (USSR).

ABSTRACT: First laboratory experiments on the application of nickel oxide in steelmaking were carried out by L. I. Aronov et al in the Moscow Institute of Steel (Stal', 1947, No.3). In the present paper the confirmation of the possibility of the application of nickel oxide in the production of nickel containing steels on 20 ton and 30 ton basic electric arc furnaces is described. The following participated in the work: G. P. Malikov, G. I. Kabakov and N. M. Shabli. Altogether 18 experimental heats of structural steel (12XН3А) and stainless steel (1X18H9T) were carried out in which pelletised nickel oxide (containing over 20% of Ni in metallic form, total content of nickel 81.0-82.0%) prepared by Yuzhuralnikel' was used. The pellets are shown in Figure 1. In 8 heats nickel oxide was added on to the slag during the oxidation period, thus using it as an oxidant and alloying

Card 1/3

133-10-8/26

Smelting of Chromium Nickel Steel Using Pelletised Nickel Oxide.

element. The recovery of nickel in metal was not lower than 98%. The character of assimilation of nickel oxide in the bath is shown in Table 1 and the oxidation of carbon in Figure 2. The influence of nickel oxide additions on the oxidation of C, P and Mn during smelting steel 12XH3A is shown in Table 2. As under the works conditions chromium nickel structural steels and stainless steels are usually produced by remelting 1 heat for 12XH3A steel and 5 heats for 1X18H9T were carried out in which nickel oxide was added to charges in the equivalent amounts to the usual additions of metallic nickel. The degree of recovery of nickel in the metal could not be established as the percentage of Ni in the nickel scrap was not known, however, the nickel content of slag after melting was not higher than 0.18%. The quality of metal so produced was tested on rolled products according to GOST 4543-48 and GOST 5632. The quality of metal was found to be satisfactory, hydrogen content of metal before tapping was the same as in the usual heats. Specific power consumption during smelting with the application of pelletised nickel oxide increased by 5-7 kWh/ton. As the cost of

Card 2/3

Smelting of Chromium Nickel Steel Using Pelletised Nickel Oxide. 133-10-8/26

than nickel H3 and H4, the use of pelletised oxide is advantageous. There are 2 tables, 2 figures and 2 references, both of which are Slavic.

ASSOCIATION: Dneprospetsstal' Works and Gipronikel'. (Zavod Dneprospetsstal' i Gipronikel')

AVAILABLE: Library of Congress

Card 3/3

137-58-6-11821

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 6, p 90 (USSR)

AUTHOR: Bobkov, T.M.

TITLE: Experiences in the Heating of the Shrinkage Head of an Ingot.
Electric Arc Heating (Opyt raboty po obogrevu pribyl'noy chasti
slitka. Elektrodugovoy obogrev)

PERIODICAL: Tr. Nauchno-tekhn. o-va chernoy metallurgii, 1957, Vol
18, pp 110-111

ABSTRACT: A description is offered of a pilot-plant installation built at the Dneprospetsstal' plant in 1956 for electric-arc heating of shrinkage heads. This equipment permits simultaneous heating of 12 ingots of 2-3 t each. The electrodes for the heating of 4 ingots, made by bottom pouring on a single drag, are carried on a common support. In preparing the installation for heating, one of the electrodes is regulated by hand, and its position relative to the metal is changed by the main controller. The other 3 electrodes have individual regulators that automatically equalize the power on all four. For automatic regulation of the given power, a set of RMD-4.5 amplidynes is used, of the type employed in three-phase electric arc furnaces. The

Card 1/2

137-58-6-11821

Experiences in the Heating (cont.)

assignment is set up on a programming mechanism. One power transformer with 5 voltage taps of from 103 to 144 v is used to feed the installation. The maximum current on the electrode is 3000 amps. In the electrical heating of shrinkage heads of 2.8-t ingots, the hot top is filled with molten metal only to one-half the normal height. A layer of slag 50-70 mm thick is applied by means of flux. When the duration of electrical heating is 1 hr 35 min, the unit consumption of electric power is ~ 30 kwh/t. The crop end was reduced by 6-7% when the assigned power was maintained and all the requirements of the electrical heating procedures were strictly adhered to.

V.P.

1. Steel--Production 2. Steel--Heating 3. Electric arcs--Applications

Card 2/2

SAMARIN, A.M.; YEFIMOV, L.M.; VESEIKOV, N.G.; ORMAN, R.Z.; SHABANOV, A.N.;
MOROZHENSKIY, L.I.; GRANAT, I.Ya.; TOCHINSKIY, A.S.; ALYAVDIN, V.A.;
DANILOV, P.M.; PETRIKEYEV, V.I.; POPOV, B.N.; BOBKOV, T.M.;
ROSTKOVSKIY, S.Ye.; GAVRISH, D.I.; D'YAKONOV, N.S.; TIMOSHPOL'SKIY,
M.M.; ROMANOV, V.D.; POCHTMAN, A.M.; MELESHKO, A.M.; PODGORETSKIY,
A.A.; OFENGENDEN, A.M.; BRONSHTEYN, V.M.; PRIDANTSEV, M.V.; LIVSHITS,
G.L.; ROZHKOVA, V.A.; RUTES, V.S.

Reports (brief annotations). Biul. TSNIICM no.18/19:15-16 '57.
(MIRA 11:4)

1. Chlen-korrespondent AN SSSR (for Samarin). 2. Tsentral'nyy
nauchno-issledovatel'skiy institut chernoy metallurgii (for Rutes,
Rostkovskiy, Pridantsev, Livshits, Rozhkov). 3. Stal'proyekt (for
Shabanov). 4. Kuznetskiy metallurgicheskiy kombinat (for Alyavdin,
Danilov, Petrikeyev). 5. Zavod "Elektrostal'" (for Popov).
6. "Dneprospetsstal'" (for Bobkov). 7. Glavogneupor Ministerstva
chernoy metallurgii SSSR (for Gavrish). 8. Planovoye upravleniye
Ministerstva chernoy metallurgii SSSR (for D'yakonov). 9. Otdel
rabochikh kadrov, truda i zarplaty Ministerstva chernoy metal-
lurgii SSSR (for Timoshpol'skiy). 10. Glavvtorchermet Ministerstva
chernoy metallurgii SSSR (for Romanov). 11. Giprostal' (for
Pochtman). 12. Zavod im. Voroshilova (for Meleshko). 13. Zavod
"Zaporozhstal'" (for Podgoretakiy). 14. Stalinskiy metallurgicheskiy
zavod (for Ofengenden). 15. Nizhne-Tagil'skiy metallurgicheskiy
kombinat (for Bronshteyn).

(Steel--Metallurgy)

BoBkov, T.

46502
207/137-59-7-14986
Translation from: Referativnyi zhurnal, Metallurgiya, 1959, Nr 7, p 34 (USSR)

AUTHORS: Chuyko, M., Kadinov, Ye., Rutkovskiy V., Zabaluyar, I., Bobkov, T.,
Burganov, V., Antipenko, O.

TITLE: New Technology in Electric Smelting of Ball Bearing Steel

PERIODICAL: Tshch.,zhov. byul. Sovnarzhos Zapoveshak. zhov. zha. r-osa, 1959, Nr 1,
pp 6-10

ABSTRACT:

A new method of ball bearing steel smelting in high-capacity (50 t) arc furnaces was developed at the "Krasnospetsstal' 60" plant. The amount of burnt-out C during the oxidation stage is 0.25%. The temperature of the metal prior to slag skimming must be about 1,500°C. The temperature of teeming (1,500-1,570°C) as measured by the plunged thermocouple. Reduction takes place under white slag. Preliminary deoxidation of the slag is performed by carbonization of the metal by 0.03-0.05% C with the use of dry ground coke. Fe-Cr and Fe-Si are added until the slag is being formed. The slag is formed through lime, refractory clay and fluorspar in a 6:2:1 proportion and amounting to 3-4% of the metal weight. Oxidation is carried out by 3-4 blends of ground coke, 75% Fe-Si powder, and lime. 0.5 kg/% aluminum powder is added to the

Card 1/2

3.
Final mixture 10 minutes prior to teeming. The slag, before teeming, contains CaO 2-2.5%, MnO 0.25 and FeO 40-45%. The metal temperature is 1,545-1,565°C. 0.5 kg/% of the slag and the metal with the slag are added. The teeming process, first, most of the slag and then the metal with the slag are added. The teeming process lasts 1 hour 30 minutes. Consumption of the slag by conventional technology and the average mark for oxides (October 1957) is 2.15 and 2.15 for sulfides. Globular impurities usually do not occur in the new technology. Duration of the smelting time is reduced by 10%; electric power consumption is reduced by 50-70 kWh/ton. V.B.

Card 2/2

BOBKOV, T. M.

5/18/60/000/008/002/018
A161/A029

AUTHORS:

Chuyko, M.M.; Rukhovskiy, V.B.; Konishchev, M.F.; Kazuyazko, A.G.; Repenilo, A.F.; Yakovlevich, I.S.; Zabaluyev, I.F.; Kuznetsov, V.V.; Zhukovskiy, M.K.; Antipenko, G.I.

TITLE:

A New Smelting Technology Under White Slag for Ball Bearing Steel of Grade M415 (SMDH15)

SYNOPSIS:

Izvestiya Vysishikh uchebnykh zavedeniy. - Chernyye metallurgiya, 1960, No. 8, pp. 38 - 47.

At the "Dnepropetral'sk" Works up to 1956 SMDH15 steel was treated simultaneously with slag and no attention was paid to steel treatment by slag in the ladle during the teeming. The final S content of 0.006 was obligatory and the refining took 2 h 10 min and 2 h 40 min or more. The refining time had been cut down to 1 h 50 min and 2 h 10 min by addition of ferrochrome into reduced metal with a content of 0.003% Cr. The cost of the heat process and to improve the metal quality, M.M. Chuyko suggested a new teeming time to 1 h 10 min or less by decarburization and desulfuration of the metal with white slag in the ladle during teeming. The article contains details of this new

Card 1/3

TECHNIQUE:

The effect of the oxidizing and reducing heat period factors was determined. The formation of highly-basic and well decarburized slag was mainly studied. The slag quantity used was 4 - 5% of the metal weight with a CaO content of over 55%, FeO below 0.4% and CaF₂ below 2.0%. First a considerable quantity of slag was spilled through a widely open hole into the ladle, and then metal poured with a height in a solid jet, which brought about a large contact area with slag and decarburization and desulfuration. The optimum parameters of the oxidation period were established: [C] = 0.003 - 0.005, carbon burning rate of 0.4 - 0.5%/h, and a metal temperature of 1,545 - 1,600°C. Before starting the oxidizing slag. The reducing period under lime-characteristic white slag with low calcium fluoride content proved to be expedient, as well as the treatment of the metal in the ladle by this slag. The optimum slag composition is: (FeO) < 0.5%; (CaF₂) = 1 - 2%; Σ(SiO₂ + Al₂O₃) = 31 - 34%; (CaO) > 53%; (FeO) < 0.2%, and Σ(CaO + MgO) = 63 - 65%. The optimum metal temperature before teeming is 1,550 - 1,570°C; it ensures the filling of a 2.8-ton ingot during 165 - 180 min. The final decarburization of steel, by aluminum in the ladle gives a high reduction of oxygen content (over 30%). The quantity of nonmetallic inclusions in

Card 2/3

RESULTS:

steel was slightly lower than usual in steel melted in the usual process under ceramic slag with long refining. There are 7 figures, 5 tables and 7 Soviet references.

ASSOCIATIONS:

Dnepropetrovskiy metallurgicheskii Institut (Dnepropetrovsk Metallurgical Institute); saved "Dnepropetral'sk" ("Dnepropetral'sk" Works)

SUBMITTED:

November 12, 1959

Card 3/3

S/133/61/000/006/007/017
A054/A129

AUTHORS: Gnuchev, S. M., Candidate of Technical Sciences, Trakhimovich, V. I.,
Tregubenko, A. F., Frantsov, V. P., Bobkov, T. M., Engineers

TITLE: Melting steel in arc-furnace with electromagnetic stirring of the
bath

PERIODICAL: Stal', ²¹no. 6, 1961, 519-522
^

TEXT: Electromagnetic stirring was first applied in the USSR, in 1956,
to a ДСВ-18 (DSV-18) type furnace (diameter of the working area: 3,070 mm,
depth of the bath: 605 mm, transformer capacity: 8,000 kw); further equipment
for stirring was installed in 1959. Tests were carried out to determine the
effect of electromagnetic stirring on the oxygen and sulfur content during the
reduction period and to examine the efficiency of this process. The metal was
stirred in such a way, (Fig. 1a) that after rising from the lower layers at the
outlet opening it spread over the bath surface while two rotation centers were
forming at the bridge. In the present series of tests the maximum rate of metal
movement was 0.25 - 0.40 m/sec at the rear furnace banks and 0.14 - 0.25 m/sec
at the frontal furnace banks, with a frequency of 0.95 - 1.0 cps. During the

Card 1/3

Melting steel in arc-furnace ...

S/133/61/000/006/007/017
A054/A129

tests the electromagnetic stirring went on for the entire period of refining. Based on the results obtained for the electromagnetic stirring of low-carbon structural steels, (12XH3A = 12KhN3A, 15XM = 15KhM) it was found that this process compared with the conventional method accelerated deoxidation considerably, viz. by 30 - 40 minutes. When deoxidizing took place for the usual period, electromagnetic stirring resulted in a more thorough deoxidation (0.003 - 0.005% oxygen content before tapping instead of 0.005 - 0.007% when applying the conventional method). Increased deoxidation by electromagnetic stirring was also recorded for stainless low-carbon steels (0.0035 - 0.0070% oxygen instead of 0.007 - 0.013% in the old process). The distribution coefficient of sulfur during reduction when applying the electromagnetic stirring method was higher, whereas the sulfur-content in the metal was lower than in the usual castings. No increase in hydrogen and nitrogen content was observed, nor did the furnace bottom display any increased wear and tear when electromagnetic stirring was applied. It was possible to accelerate the skimming of slag by 5-10 minutes, which increased the furnace capacity by 10%; moreover, manual labor could be entirely eliminated from this process. The temperature of the metal reached an average value more quickly and could be controlled more easily than in the usual manner. The bath also had a more uniform chemical composition. All these factors

Card 2/3

Melting steel in arc-furnace ...

S/133/61/000/006/007/017
A054/A129

improved the quality of the metal considerably. It was found that the waste decreased in electromagnetically stirred molten metals. This could be established for 18XHBA (18KhNVA), 12XH3A (12KhN3A), 40XHMA (40KhNMA) steels. The waste in ball bearing steel decreased also, as a result of the drop in globular inclusions, whereas the oxide and sulfide impurities occur in about the same amounts in both processes. The drawbacks of the electromagnetic stirring equipment are: 1) the air-cooling of the stators is insufficient and does not prevent their overheating; 2) on account of the slow motion of the metal at the bath surface it is not possible to mechanize the stirring of slag. For this purpose it would be necessary to raise the current intensity in the stator above the nominal value and to intensify cooling suddenly; 3) in the present construction the bath must first be removed when repairs are necessary, when the stator has to be mounted or dismantled. There are 3 figures, 4 tables and 2 Soviet-bloc references.




Fig. 1a: Scheme of the metal-circulation in the bath applied in the tests

Card 3/3

ALEKSEYENKO, M.F.; BANAS, P.S.; BOBKOV, T.M.; NATAPOV, B.S.; RYABTSEV, S.I.;
SKLYAROV, P.I.; FRANTSOV, V.P.; YUDOVICH, S.Z.; PRONIN, V.Ye.

DI-1 stainless steel. Stal' 23 no.2:159-162 F '63. (MIRA 16:2)
(Steel, Stainless)

L 18651-63 EWP(q)/EWT(m)/BDS AFFTC/ASD JD/JG
ACCESSION NR: AP3004789 S/0129/63/000/008/0055/0059 68

AUTHOR: Bobkov, T. M.; Moshkevich, Ye. M.; Gunaza, K. P.; Zlatkina, V. I. 62

TITLE: Effect of additions of rare-earth metals and their oxides on properties of some stainless steels 62

SOURCE: Metallovedeniye i termicheskaya obrabotka metallov, no. 8, 1963, 55-59

TOPIC TAGS: stainless steel, Kh18N10T steel, AISI 321 steel, Kh25N18 steel, AISI 310 steel, Kh17N13M2T steel, AISI 316T steel, misch metal effect, ferrocerium effect, lanthanum effect, cerium dioxide effect, lanthanum oxide effect, praseodymium oxide effect, steel hot ductility, steel structure, nonmetallic-inclusion content, cast structure, ingot structure

ABSTRACT: The effect of addition of 0.05--0.35% misch metal [50% Ce, 25% La, and 25% various rare-earth metals] or 0.05--0.4% ferrocerium, lanthanum, cerium dioxide, lanthanum oxide, and praseodymium oxide on structure, phase composition, amount of nonmetallic inclusions, room-temperature mechanical properties, and hot ductility of Kh18N10T [AISI 321], Kh25N18 [AISI 310], and Kh17N13M2T [AISI 316] stainless steels has been investigated. None of

Card 1/2

L 18651-63

ACCESSION NR: AP3004789

the additions was found to have a significant effect on the crystal structure of ingots of any steel tested. The forged metal had a fine-grained structure with a low content of oxide and sulfide inclusions. A 0.15—0.25% addition of misch metal reduced the amount of carbonitride inclusions in all steels tested. Kh18N10T steel containing 0.1% misch metal had improved hot ductility. In the Kh23N18 steel addition of 0.3 and 0.05% misch metal improved the ductility at 1100—1250 and 1000C, respectively. Addition of 0.05—0.15% misch metal or 0.15—0.30% La improved ductility of Kh17N13M2T steel at 1000C. Addition of ferrocium, lanthanum, cerium dioxide, lanthanum or praseodymium oxides brought about no improvement in hot ductility or room-temperature mechanical properties of Kh17N13M2T steel. Orig. art. has: 4 figures and 1 table.

ASSOCIATION: Zavod Dneprospetsstal' (Dneprospetsstal' Plant)

SUBMITTED: 00

DATE ACQ: 06Sep63

ENCL: 00

SUB CODE: ML

NO REF SOV: 000

OTHER: 000

Card 2/2

BOBKOV, T.M.; MOSHKEVICH, Ye.M.; GUNAZA, K.P.; ZLATKINA, V.I.

Effect of additions of rare-earth metals and their oxides on
the properties of certain stainless steels. Metalloved. i
term. obr. met. no.8:55-59 Ag '63. (MIRA 16:10)

1. Zavod Dneprospetsstal'.

BOBKOV, V.

Dairying - Apparatus and Supplies

Twin-duct brine coolers
Mol. prom. 13, no. 2, 1952

1. BOBKOV, V.
2. USSR (600)
4. Ice - Manufacture
7. Mechanization of crushing and loading operations at ice-making plants.
Khol. tekhn. 29 no. 3, 1952

9. Monthly List of Russian Accessions, Library of Congress, January 1953. Unclassified.

BOBKOV, V. ~~and~~ tekhn. nauk

Machines for icing food products. Khol. tekhn. 35 no.2:38-42 Mr-Ap
'58. (MIRA 11:4)

(Ice) (Food--Preservation)

BOBKOV, V.A.

Ice Industry

Breaking up ice beds with drill and explosives
Ryb. khoz., 28, no. 2, 1952

BOBKOV, V., Magd.tekhn.nauk

VNIKhI snow icing machine. Khol.tekh. 37 no.1:14-17 Ja-F
'60. (MIRA 13:5)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut kholodil'noy
promyshlennosti.
(Ice)

BOBKOV, Vsevolod Andreyevich, kand. tekhn. nauk, starshiy nauchnyy sotr.;
LAVROVA, V.V., kand. tekhn. nauk, nauchnyy red.; KAPLUN, M.S., red.;
MAMONTOVA, N.N., tekhn. red.

[Automatic ice machine for making crushed kitchen ice; scientific report] Issledovanie avtomaticheskogo l'dogeneratora dlia proizvodstva droblenogo pishchevogo l'da; nauchnoe soobshchenie. Moskva, Gos. izd-vo torg. lit-ry, 1961. 31 p. (MIRA 14:12)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut kholodil'noy promyshlennosti im. A.I.Mikoyana (for Bobkov).
(Ice—Manufacture)

BOBKOV, Vsevolod Andreyevich, kand. tekhn. nauk; CHICHKOV, N.V., red.;
EL'KINA, E.M., tekhn. red.

[Manufacture of ice and its uses] Proizvodstvo i primeneni
vodnogo l'da. Moskva, Gos.izd-vo tog. lit-ry, 1961. 165 p.
(MIRA 14:5)

(Ice--Manufacture)

BOBKOV, V.A., kand.tekhn.nauk

CL-25 automatic flake ice maker for food enterprises. Khol. tekhn.
38 no.4:28-33 JI-Ag '61. (MIRA 15:1)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut kholodil'noy
promyshlennosti im. A.I.Mikoyana.
(Ice--Manufacture)

BOBKOV, V.A.; DANILOV, R.L.; DRACHEVA, T.A.; NOSKOVA, G.L.;
OLENEV, Yu.A.; KHOLOPOVA, A.A.; SHE LAPUTIN, V.I.; RYUTOV, D.G., red.;
BYKOVA, M.G., red.; OKOLELOVA, Z.P., tekhn. red.

[Use of refrigeration for the preservation of agricultural products] Primenenie kholoda dlia khraneniia sel'skokho-
ziaistvennykh produktov. Moskva, Sel'khozizdat, 1963. 53 p.
(MIRA 16:12)

1. Nauchnyye sotrudniki Vsesoyuznogo nauchno-issledovatel'-
skogo instituta kholodil'noy promyshlennosti (for all except
Bykova, Okolelova).

(Farm produce—Storage)

BOBKOV, V.A.; SMOLENSKIY, G.A.; KIZHAYEV, S.A.; MYL'NIKOVA, I.Ye.

Magnetic and electric properties of ferroelectric yttrium and ytterbium manganates. Fiz. tver. tela 5 no.12:3607-3609 D '63. (MIRA 17:2)

1. Institut poluprovodnikov AN SSSR, Leningrad.

CHUYEV, Aleksey Vasil'yevich; CHERTETSOV, Vasilii Nikolayevich;
SOKHOR, Izabella Naumovna; BOBKOV, V.A., red.

[Work practice of the Leningrad Economic Region Council
of Innovators] Opyt raboty sovetov novatorov Leningrad-
skogo ekonomicheskogo raiona. Leningrad, 1965. 41 p.
(MIRA 18:5)